

WARNING!

Warning: Flammable liquid and vapor.

Warning: May cause respiratory irritation

Warning: Harmful if swallowed

Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. Harmful in contact with skin. May cause damage to organs (auditory system) through prolonged or repeated exposure. Harmful to aquatic life.

PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/.../equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. IF ON SKIN (or hair):

Remove/Take off immediately all contaminated clothing. Rinse SKIN with water/shower. In case of fire: Use Foam, alcohol foam, CO2, dry chemical, water fog for extinction. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If inhaled, call a POISON CENTER or doctor/physician if you feel unwell. IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice/attention. Get medical advice/attention if you feel unwell. Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

TO FIGHT FIRE:

Solvent may produce excessive pressure during a fire causing sealed containers to rupture and ignite. Cool fire exposed containers with water. Fight fire with CO2, foam, alcohol foam or dry chemical. Fire fighters should wear a self-contained breathing apparatus and full face piece when fighting fire. Hazardous decomposition products may be toxic materials, carbon dioxide, carbon monoxide, etc. Water may not be effective for fighting fires.



GARON

GARON PRODUCTS, INC
PO BOX 1924, WALL NJ 07719
1-800-631-5380 - www.garonproducts.com

GARON

HI-GLOSS™

For Industrial Use Only

ALIPHATIC POLYURETHANE, VOC COMPLIANT TOPCOAT
TWO PART URETHANE

**MIXING: 2 GALLONS PART A to 1 GALLON (8.5#) PART B
(volumes approximate)**

POT LIFE: 1.5 Gallon Volume: 2 to 4 hours @ 70°F.

HIGHER TEMPERATURES DECREASE POT LIFE

A

Base
Component

Read carefully other cautions on side panel.
KEEP OUT OF THE REACH OF CHILDREN

Lot Number:

**HEALTH:
REACTIVITY: 2
0**

**FLAMMABILITY: 3
PERSONAL PROTECTION: G**

CHEMICAL CONTENT:

Propylene Glycol Monomethyl Ether Acetate CAS# 108-65-6, Saturated Polyester Polyol (non-hazardous) CAS# unknown, POLYESTER POLYOL NJTSRNS0001C, Siloxanes and silicones, di-me reactions products with silica CAAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9, Xylene CAS# 1330-20-7, 2,6-Dimethyl-4-Heptanone CAS# 108-83-8, Ethyl benzene CAS# 100-41-4, polyalkylene glycol CAS# 9038-95-3, 4,6-dimethyl-2-heptanone CAS# 19549-80-5, Dibutyltin Dilurate CAS# 77-58-7, Cellulose Acetate Butyrate CAS# 9004-36-8, Methyl N-Amyl Ketone CAS# 110-43-0, Ethyl 3-Ethoxypropionate CAS# 763-69-9, Additive NJTSRN 800963-5023m, Colors May Contain: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4, Acrylic polymers (non-hazardous) CAS# trade secret, C.I. Pigment violet 19 CAS# 1047-16-1, Barium Sulfate CAS# 7727-43-7, zinc salt of alkyl naphalene sulfonic acid CAS# undisclosed, solvent naptha CAS# 64742-88-7, polyamine polyester polymer (non hazardous), C.I. Pigment blue 15 CAS# 147-14-8, C.I. Pigment Blue CAS# 25869-00-5, C11-C13 isoparaffin CAS# 64741-65-7, C.I. Pigment green 17 CAS# 1308-38-9, Alkyl polyether phosphate ester CAS# trade secret, C.I. Pigment green 7, CAS# 1328-53-6, C.I. Pigment green 36 CAS# 14302-13-7, C.I. Pigment Yellow CAS# 4531-49-1, C.I. Pigment Yellow CAS# 5567-15-7, C.I. Pigment yellow 42 CAS# 51274-00-1, pigment orange CAS# 15793-73-4, C.I. Pigment red 101 CAS# 1309-37-1, C.I. Pigment red 3 CAS# 2425-85-6, aluminum silicate dehydrate CAS# 1332-58-7, mineral spirits CAS# 8052-41-3, C.I. Pigment red 187 CAS# 59487-23-9,

APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Store product at normal room temperature. Make sure the substrate is dry and properly prepared. Remove all contaminants and curing compounds. Apply material between 50-90 degrees F. Colder temperatures will require a longer cure time. Apply a suitable primer. Mix part A and part B together thoroughly (make sure the mix ratio is correct). Apply to primed surface with brush or roller. If recoating after 24 hours, the floor should be de-glossed to assure proper adhesion. Check all preceding and subsequent coats for foreign contamination or epoxy blishes. Apply material with relative humidity below 90%.

DOT: UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, ETHYL BENZENE), 3, PG III

IMO/IMDG: UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, ETHYL BENZENE), 3, PG III

NOTICE TO BUYER:

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at www.garonproducts.com

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. This material has a maximum VOC of 335 grams per liter.