

**DANGER!**  
Flammable liquid and vapor. May cause respiratory irritation. May cause damage to organs (auditory) through prolonged or repeated exposure. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled  
Harmful to aquatic life. Harmful to aquatic life with long lasting effects

**PRECAUTIONARY STATEMENTS:**  
Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/.../equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapours/spray. Wear respiratory protection. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves and clothing to prevent skin contact. Avoid release to the environment. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. In case of fire: Use Foam, alcohol foam, CO2, dry chemical for extinction. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. If inhaled, Call a POISON CENTER or doctor/physician if you feel unwell. Get medical advice/attention if you feel unwell. IF ON SKIN: wash with plenty of soap and water. Call a POISON CENTER or doctor/physician if you feel unwell. Take off immediately all contaminated clothing and wash it before reuse. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. IF experiencing respiratory symptoms: call a POISON CENTER or doctor/physician. IF SKIN irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

**TO FIGHT FIRE:**  
Solvent may produce excessive pressure during a fire causing sealed containers to rupture and ignite. Cool fire exposed containers with water. Fight fire with CO2, foam, alcohol foam or dry chemical. Fire fighters should wear a self-contained breathing apparatus and full face piece when fighting fire. Hazardous decomposition products may be toxic materials, carbon dioxide, carbon monoxide, etc. Water may not be effective for fighting fires.



**GARON**

GARON PRODUCTS, INC  
PO BOX 1924, WALL NJ 07719  
1-800-631-5380 - [www.garonproducts.com](http://www.garonproducts.com)

**GARON**

**HI-GLOSS™**

For Industrial Use Only

ALIPHATIC POLYURETHANE, VOC COMPLIANT TOPCOAT  
TWO PART URETHANE

**MIXING: 2 GALLONS PART A to 1 GALLON (8.5#) PART B  
(volumes approximate)**

**POT LIFE: 1.5 Gallon Volume: 2 to 4 hours @ 70°F.  
HIGHER TEMPERATURES DECREASE POT LIFE**

**B**

Hardener  
Component

Read carefully other cautions on side panel.  
**KEEP OUT OF THE REACH OF CHILDREN**

Lot Number:

**HEALTH: 2 FLAMMABILITY: 3**  
**REACTIVITY: 1 PERSONAL PROTECTION: G**

**CHEMICAL CONTENT:**  
Hopolymer of HDI CAS# 28182-81-2, Xylene CAS# 1330-20-7, Ethyl benzene CAS# 100-41-4, n-Butyl Acetate CAS# 123-86-4, Hexamethylene Diisocyanate (HDI) CAS# 822-06-0,  
**APPLICATION PROCEDURES:**  
Request and read the technical data sheet before use. Store product at normal room temperature. Make sure the substrate is dry and properly prepared. Remove all contaminants and curing compounds. Apply material between 50-90 degrees F. Colder temperatures will require a longer cure time. Apply a suitable primer. Mix part A and part B together thoroughly (make sure the mix ratio is correct). Apply to primed surface with brush or roller. If recoating after 24 hours, the floor should be de-glossed to assure proper adhesion. Check all preceding and subsequent coats for foreign contamination or epoxy blushes. Apply material with relative humidity below 90%.

**DOT:** UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, BUTYL ACETATE), 3, PG III  
**IMO/IMDG:** UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, BUTYL ACETATE), 3, PG III  
**NOTICE TO BUYER:**

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at [www.garonproducts.com](http://www.garonproducts.com)  
Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material.  
This material has a maximum VOC of 335 grams per liter.