

**DANGER!**

Flammable liquid and vapor. May Cause an allergic skin reaction. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Causes skin irritation. Causes serious eye irritation. Suspected of causing genetic defects. Suspected of causing cancer. May cause Respiratory irritation or may cause drowsiness or dizziness. May cause damage to organs (liver, kidney, nervous system, respiratory system, liver, central nervous system, lungs) through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS:**

IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. IF experiencing respiratory symptoms: call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use FOAM, ALCOHOL FOAM, CO<sub>2</sub>, WATER FOG for extinction. IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell. Store locked up. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

**TO FIGHT FIRE:**

Solvent may produce excessive pressure during a fire causing sealed containers to rupture and ignite. Cool fire exposed containers with water. Fight fire with CO<sub>2</sub>, foam, alcohol foam or dry chemical. Fire fighters should wear a self-contained breathing apparatus and full face piece when fighting fire. Hazardous decomposition products may be carbon dioxide, carbon monoxide, NOX, HCN, and other toxic chemicals. Water may not be effective for fighting fires.



**GARON**

GARON PRODUCTS, INC  
PO BOX 1924, WALL NJ 07719  
1-800-631-5380 - [www.garonproducts.com](http://www.garonproducts.com)

**GARON**

**ACCELA RESIN 85™**

For Industrial Use Only

POLYASPARTIC COATING  
TWO PART URETHANE

**MIXING: 2 parts A to 1 part B by volume (volumes approximate)**

**POT LIFE: 150 gram mass: 30 to 60 minutes 100 gram mass: 1 to 4 minutes @ 70°F. (actual usable working time is 15-20 minutes)**

**HIGHER TEMPERATURES & LARGER VOLUMES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.  
**KEEP OUT OF THE REACH OF CHILDREN**

**HEALTH:  
REACTIVITY:**

**3  
1**

**FLAMMABILITY:  
PERSONAL PROTECTION:**

**2  
G**

**CHEMICAL CONTENT:**

CYCLOALIPHATIC DIAMINE CAS# 136210-30-5, ALIPHATIC CARBOXYLIC ESTER CAS# 623-91-6, AROMATIC PETROLEUM DISTILLATES CAS# 64742-95-6, cumene CAS# 98-82-8, \*1,2,4-Trimethylbenzene CAS# 95-63-6, ethyl benzene CAS# 100-41-4, Xylene CAS# 1330-20-7, HOMOPOLYMER OF HDI CAS# 28182-81-2, HEXAMETHYLENE DIISOCYANATE (HDI) CAS# 822-06-0,

**APPLICATION PROCEDURES:**

Request and read the technical data sheet before use. Apply with a brush or roller tool. This product is intended for a thin mil build coating only. Always apply a test area to determine suitability for adhesion and compatibility prior to using. The cure rate and gel time can be influenced by humidity. Read the technical data before using.

**DOT:** Part A: UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS AROMATIC PETROLEUM DISTILLATES), 3, PG III. Part B: Not Regulated.

**IMO/IMDG:** Part A: UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS AROMATIC PETROLEUM DISTILLATES), 3, PG III. Part B: Not Regulated.

**NOTICE TO BUYER:**

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at [www.garonproducts.com](http://www.garonproducts.com) Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use.

However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. This material has a maximum VOC of 159 grams per liter.