

DANGER!

May cause cancer. Causes damage to organs through prolonged or repeated exposures (lungs, respiratory system). May cause respiratory irritation. Harmful if swallowed. Harmful in contact with skin. Causes serious eye damage. May cause an allergic skin reaction.

Causes severe skin burns and eye damage.

Suspected of damaging fertility of the unborn child.

Toxic to aquatic life

PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid release to the environment. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell. Rinse mouth. IF ON SKIN:

wash with plenty of soap and water. Call a POISON CENTER or doctor/physician if you feel unwell. Take off immediately all contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If in eyes, immediately call a POISON CENTER or doctor/physician. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. If skin irritation or burns develop, Call a doctor/physician . IF exposed or concerned: Get medical advice/attention.

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

TO FIGHT FIRE:

Fight fire with CO2, foam, dry chemical or water fog. Hazardous decomposition products may be CO2, CO, acids, aldehyde and NOX compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.



GARON

GARON PRODUCTS, INC
PO BOX 1924, WALL NJ 07719
1-800-631-5380 - www.garonproducts.com

GARON

ARCTIC FREEZITE™

For Industrial Use Only

ARCTIC FORMULATION
THREE PART MORTAR

MIXING: 2# PART A TO 0.9# PART B AND AGGREGATE

POT LIFE: .125 cu. Ft. mix: 2 to 4 minutes @ 70°F.
HIGHER TEMPERATURES DECREASE POT LIFE

Lot Number:

Read carefully other cautions on side panel.
KEEP OUT OF THE REACH OF CHILDREN

HEALTH:
REACTIVITY: 2
0

FLAMMABILITY: 1
PERSONAL PROTECTION: G

CHEMICAL CONTENT:

SILICON DIOXIDE CAS# 14808-60-7, DIETHYLENTRIAMINE CAS# 111-40-0, BISPHENOL A CAS# 80-05-7, BENZYL ALCOHOL CAS# 100-51-6, MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, Acrylate Inhibited with 100ppm Ether Hydroquinone CAS# 15625-89-5, Colors may contain: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4, Precipitated Silica CAS# 112926-00-8, Iron III oxide CAS# 1309-37-1, Yellow Pigment CAS# Not available, Zinc Sulfide CAS# 1314-98-3, Barium Sulfate CAS# 7727-43-7, Pigment yellow 65 CAS# 6528-34-3, Iron III hydroxide CAS# 20344-49-4, C.I. Pigment Blue CAS# 147-14-8, Aluminum Oxide CAS# 1344-28-1, Silica, amorphous CAS# 7631-86-9, Iron Oxide Yellow CAS# 51274-00-1

APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Properly prepare the surface and remove all contaminants. Make sure the floor is dry. Store material at normal room temperature (55-70 degrees F) prior to using. Be prepared to work in a fast and organized manner as this product will set up in a very short time (2-5 minutes). First, take the material into the cold storage area. Mix the part A and part B together as quickly as possible. Next, add in the provided aggregate immediately. Mix the material to a mortar consistency as quickly as possible. Finally, apply the mixed material by trowel or other suitable equipment immediately and quickly. This material can be applied in areas where temperatures are as low as -10F.

DOT: Part A: Not Regulated. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS DIETHYLENTRIAMINE), 8, PG III. Part C: Not Regulated.

IMO/IMDG: Part A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer) , 9, PGIII, MARINE POLLUTANT. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS DIETHYLENTRIAMINE, BISPHENOL A), 8, PG III, MARINE POLLUTANT. Part C: Not Regulated.

NOTICE TO BUYER:

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at www.garonproducts.com

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material.

This material has a maximum VOC of zero grams per liter.