

DANGER!

Harmful if swallowed. May cause damage to organs through prolonged or repeated exposure (skin, central nervous system (CNS) . Causes Severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage.

Warning: Harmful if inhaled. Suspected of damaging the fertility of the unborn child.

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product. Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection.

Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Avoid release to the environment.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. If skin irritation or burns develop, Call a doctor/physician . If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell. Rinse mouth. Get medical advice/attention if you feel unwell. If in eyes, immediately call a POISON CENTER or doctor/physician.

IF ON SKIN: wash with plenty of soap and water.

IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Call a POISON CENTER or doctor/physician if you feel unwell. Collect spillage.

Store locked up. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

TO FIGHT FIRE:

Fight fire with CO2, foam, dry chemical or water fog. Hazardous decomposition products may be CO2, CO, acids, aldehyde and NOX compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.



GARON

GARON PRODUCTS, INC
PO BOX 1924, WALL NJ 07719
1-800-631-5380 - www.garonproducts.com

GARON

FAST CURE™

For Industrial Use Only

**HIGH BUILD, QUICK SET COATING
TWO PART EPOXY**

MIXING: 9.1# PART A TO 4.25# PART B (weight for some colors such as white might vary) (2 parts A to 1 part B by volume) (volumes approximate)

**POT LIFE: 1 Gallon Volume: 15-20 minutes @ 70°F.
HIGHER TEMPERATURES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.
KEEP OUT OF THE REACH OF CHILDREN

HEALTH: 2 **FLAMMABILITY: 1**
REACTIVITY: 0 **PERSONAL PROTECTION: G**

CHEMICAL CONTENT:

BENZYL ALCOHOL CAS# 100-51-6, 3-AMINOMETHYL-3,5,5-TRIMETHYL CYCLOHEXANE CAS# 2855-13-2, NONYL PHENOL CAS# 84852-15-3, M-XYLENE DIAMINE CAS# 1477-55-0, BENZENEMETHANAMINE, N,N-DIMETHYL-BENZYLDIMETHYLAMINE CAS# 103-83-3, accelerator NJTSRN 29943300001-5715P, MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, Siloxanes and silicones, di-me reactions products with silica CAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9, BISPHENOL F/EPICHLOROHYDRIN EPOXY RESIN CAS# 9003-36-5, STODDARD SOLVENT CAS# 8052-41-3, 1-Methoxy-2-Propanol Acetate CAS# 108-65-6, 1,2,4-Trimethylbenzene CAS# 95-63-6, Additive NJTSRN 800963-5023, Solvent naphtha, petroleum, heavy aromatic CAS# 64742-94-5, PROPYLENE GLYCOL MONOMETHYL ETHER CAS# 107-98-2, COLORS MAY CONTAIN: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4, Silicon Dioxide CAS# 7631-86-9, Ferric Oxide CAS# 1309-37-1, Iron III hydroxide CAS# 20344-49-4, Yellow Pigment CAS# not available, Zinc Sulfide (component of yellow pigment) CAS# 1314-98-3, Barium Sulfate (component of yellow pigment) CAS# 7727-43-7, Pigment yellow 65 (component of yellow pigment) CAS# 6528-34-3, C.I. Pigment Blue CAS# 147-14-8, Aluminum Oxide CAS# 1344-28-1, Iron Oxide Yellow CAS# 51274-00-1.

APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the floor surface is dry. Store all material at room temperature before using. Apply an appropriate primer. Apply material between 50-90 degrees F (mix only an amount that can be used in a short period of time). Check preceding coats and subsequent coats for blushes. Mix the part A and part B together thoroughly (make sure the mix ratio is correct). Apply the material by brush, or roller. Use an air release roller tool to remove entrapped air before coating tacks off.

DOT: Part A: Not Regulated. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS M-XYLENE DIAMINE, NONYL PHENOL), 8, PG III, MARINE POLLUTANT..

IMO/IMDG: Part A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer) , 9, PGIII, MARINE POLLUTANT. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS M-XYLENE DIAMINE, NONYL PHENOL), 8, PG III, MARINE POLLUTANT.

NOTICE TO BUYER:

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at www.garonproducts.com

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. This material has a maximum VOC of 36 grams per liter.