

**DANGER!**

Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life. Toxic to aquatic life with long lasting effects

**PRECAUTIONARY STATEMENTS:**

Keep out of reach of children. Read label before use. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. If skin irritation or burns develop, Call a doctor/physician . If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If in eyes, immediately call a POISON CENTER or doctor/physician.

Store locked up. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

**TO FIGHT FIRE:**

Fight fire with CO2, foam, dry chemical or water fog. Hazardous decomposition products may be CO2, CO, acids, aldehyde and NOX compounds or byproducts. Fire fighters should wear a self-contained breathing apparatus.



**GARON**

GARON PRODUCTS, INC  
PO BOX 1924, WALL NJ 07719  
1-800-631-5380 - [www.garonproducts.com](http://www.garonproducts.com)

**GARON**

**GARON GLAZE™**

For Industrial Use Only

HIGH BUILD, CLEAR  
TWO PART EPOXY

**MIXING: 9.0# PART A TO 4.15# PART B**

**POT LIFE: 1.5 Gallon Volume: 20-30 minutes @ 70°F.  
HIGHER TEMPERATURES & LARGER VOLUMES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.  
**KEEP OUT OF THE REACH OF CHILDREN**

**HEALTH: 2**      **FLAMMABILITY: 1**  
**REACTIVITY: 0**      **PERSONAL PROTECTION: G**

**CHEMICAL CONTENT:**

BENZYL ALCOHOL CAS# 100-51-6, 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXANE CAS# 2855-13-2, 2-HYDROXYBENZOIC ACID CAS# 69-72-7, CYCLOALIPHATIC AMINE ADDUCT CAS# 68609-08-5, MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, 2-propenoic acid, 2-[Methyl](nonafluorobutyl)sulfonyl]amino]ethyl ester, telomere with mrihyloxirane polymer with oxirane di-2-propenoate and methyloxirane polymer with oxirane mono-prpenoate CAS# 1017237-78-3, 1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-n-(2-hydroxyethyl)-N-methyl- CAS# 34454-97-2, 2-propenoic acid, 2-[methyl]nonafluorobutyl)sulfonyl]amino]ethyl ester CAS# 67584-55-8, polyether polymer NJTSRN 04499600-6437, 2-methoxymethylethoxypropanol CAS# 34590-94-8, toluene CAS# 108-88-3, 1,2-Propanediol CAS# 57-55-6, Oxirane, Me, polymer with oxirane monobutyl ether CAS# 9038-95-3, Siloxanes and silicones, di-me reactions products with silica CAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9, BENZYL ALCOHOL CAS# 100-51-6, NONYL PHENOL CAS# 84852-15-3, Additive NJTSRN 800963-5023.

**APPLICATION PROCEDURES:**

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the floor surface is dry. Store materials at room temperature before using. Apply an appropriate primer. Apply material between 55-90 degrees F, lower temperatures will require more time for material to cure. Check preceding coats and subsequent coats for blushes. Mix the part A and part B together thoroughly (make sure the mix ratio is correct). Apply the material by brush or roller. Use an air release roller tool to remove entrapped air. After application, keep the floor dry for seven days (time for the coating to fully cure). Apply with relative humidity below 85% for best results.

**DOT:** Part A: Not Regulated. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE), 8, PG III.

**IMO/IMDG:** Part A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer) , 9, PGIII, MARINE POLLUTANT. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, BENZYL ALCOHOL), 8, PG III, MARINE POLLUTANT.

**NOTICE TO BUYER:**

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at [www.garonproducts.com](http://www.garonproducts.com)

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. This material has a maximum VOC of 2 grams per liter.