

DANGER!

Flammable liquid and vapor. May causes drowsiness or dizziness. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage.

Harmful to aquatic life. Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/.../equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Avoid release to the environment. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. In case of fire: Use FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL for extinction. Store in a well-ventilated place. Keep cool. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. If skin irritation or burns develop, Call a doctor/physician . If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If in eyes, immediately call a POISON CENTER or doctor/physician. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Collect spillage. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

TO FIGHT FIRE:

Fight fire with CO2, foam, dry chemical or water fog. Hazardous decomposition products may be CO2, CO, acid, aldehyde and NOX compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.



GARON

GARON PRODUCTS, INC
PO BOX 1924, WALL NJ 07719
1-800-631-5380 - www.garonproducts.com

GARON

GARON GUARD™

For Industrial Use Only

HIGH BUILD, COATING TWO PART EPOXY

**MIXING: 12# PART A TO 3.85# PART B (BY WEIGHT) TWO PARTS
A TO ONE PART B (BY VOLUME) (VOLUMES APPROXIMATE)**

POT LIFE: 1.5 Gallon Volume: 35-55 minutes 150 Gram Mass: Minimum 1 hour 1 gallon volume: 1 to 2 hours @ 70°F.

HIGHER TEMPERATURES DECREASE POT LIFE

Lot Number:

Read carefully other cautions on side panel.
KEEP OUT OF THE REACH OF CHILDREN

HEALTH: 3 **FLAMMABILITY: 2**
REACTIVITY: 0 **PERSONAL PROTECTION: G**

CHEMICAL CONTENT:

BENZYL ALCOHOL CAS# 100-51-6, 3-AMINOMETHYL-3,5,5-TRIMETHYL CYCLOHEXANE CAS# 2855-13-2, 2-HYDROXYBENZOIC ACID CAS# 69-72-7, TRIS-2,4,6-DIMETHYLAMINOMETHYLPHENOL CAS# 90-72-2, Bis(dimethylaminomethyl) phenol CAS# 71074-89-0, PROPYLENE GLYCOL MONOMETHYL ETHER CAS# 107-98-2, , n-Butyl acetate, CAS# 123-86-4, butan-2-ol CAS# 78-92-2, Propylene glycol derivative CAS# Trade Secret, 1,4-dioxane CAS# 123-91-1, MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, Talc CAS# 14807-96-6, crystalline silica CAS# 14808-60-7, LIMESTONE CAS# 1317-65-3, XYLENE CAS# 1330-20-7, ethyl benzene CAS# 100-41-4, Siloxanes and silicones, di-me reactions products with silica CAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9, COLORS MAY CONTAIN: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4, Silicon Dioxide CAS# 7631-86-9, Ferric Oxide CAS# 1309-37-1, Iron III hydroxide CAS# 20344-49-4, Yellow Pigment CAS# not available, Zinc Sulfide (component of yellow pigment) CAS# 1314-98-3, Barium Sulfate (component of yellow pigment) CAS# 7727-43-7, Pigment yellow 65 (component of yellow pigment) CAS# 6528-34-3, C.I. Pigment Blue CAS# 147-14-8, Aluminum Oxide CAS# 1344-28-1, Iron Oxide Yellow CAS# 51274-00-1.

APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the floor surface is dry. Store material at room temperature before using. Apply material with temperatures between 60 and 90 degrees F, lower temperatures will require more time for the material to cure. Check preceding coats and subsequent coats for blushes. Mix the part A and part B together thoroughly (make sure the mix ratio is correct). Apply the material by brush or roller. Use an air release roller tool to remove entrapped air. Apply a suitable topcoat.

DOT: Part A: Not Regulated. Part B: UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS PROPYLENE GLYCOL MONOMETHYL ETHER), 3, PG III.

IMO/IMDG: Part A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PG III, MARINE POLLUTANT. Part B: UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS PROPYLENE GLYCOL MONOMETHYL ETHER, ISOPHORONE DIAMINE), 3, PG III, MARINE POLLUTANT.

NOTICE TO BUYER:

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at www.garonproducts.com
Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. This material has a maximum VOC of 95 grams per liter.