

**DANGER!**

Causes serious eye damage. Harmful if swallowed. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Harmful if inhaled. Harmful to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS:**

Keep out of reach of children. Read label before use. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection to prevent skin contact. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. If skin irritation or burns develop, Call a doctor/physician. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes, immediately call a POISON CENTER or doctor/physician.

Collect spillage. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

**TO FIGHT FIRE:**

Fight fire with CO<sub>2</sub>, foam, dry chemical or water fog. Hazardous decomposition products may be CO<sub>2</sub>, CO and NO<sub>x</sub> compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.



**GARON**

GARON PRODUCTS, INC  
PO BOX 1924, WALL NJ 07719  
1-800-631-5380 - [www.garonproducts.com](http://www.garonproducts.com)

**GARON**

**GARON SEAL HCR™**

For Industrial Use Only

PROCESS INJECTION EPOXY  
TWO PART EPOXY

**MIXING: 9.2# (gallon) part A with 3.95# (1/2 gallon) part B (volumes approximate)**  
**POT LIFE: 1.5 Gallon Volume: greater than 40 minutes**  
**HIGHER TEMPERATURES & LARGER VOLUMES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.  
**KEEP OUT OF THE REACH OF CHILDREN**

**HEALTH:** 2  
**REACTIVITY:** 0

**FLAMMABILITY:** 1  
**PERSONAL PROTECTION:** G

**CHEMICAL CONTENT:**

TETRAETHYLENE PENTAMINE CAS# 112-57-2, TOFA, REACTION PRODUCTS WITH TEPA CAS# 68953-36-6, MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, Siloxanes and silicones, di-me reactions products with silica CAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9.

**APPLICATION PROCEDURES:**

Request and read the technical data sheet before use. Bring material to normal room temperature. Remove any loose concrete or previous joint compound leaving a clean sound repair area. Apply material with temperatures between 50-110 degrees F. Attach injection ports along the surface of the crack to be repaired and seal the outer surface of the crack with a suitable material. Allow sufficient time for the material placed on the outer surface to cure prior to starting the injection process. Apply the product by injecting the mixed material into the attached ports starting from the bottom and working upward. After the material has reached the port directly above the port where injecting, plug the port and move to the next port, etc.

**DOT:** Part A: Not Regulated. Part B: Not Regulated.

**IMO/IMDG:** Part A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PG III, MARINE POLLUTANT. Part B: Not Regulated.

**NOTICE TO BUYER:**

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at [www.garonproducts.com](http://www.garonproducts.com). Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. This material has a maximum VOC of zero gram per liter.