

DANGER!

Flammable liquid and vapor. Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Harmful if inhaled. May cause respiratory irritation. May be corrosive to metals. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/.../equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Do not breathe dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Keep only in original container. Wear respiratory protection. Avoid release to the environment. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. In case of fire: Use Foam, alcohol foam, CO₂, dry chemical for extinction. IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell. Rinse mouth. IF ON SKIN: wash with plenty of soap and water. Call a POISON CENTER or doctor/physician if you feel unwell. Take off immediately all contaminated clothing and wash it before reuse. P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. IF experiencing respiratory symptoms: call a POISON CENTER or doctor/physician. If skin irritation or burns develop, Call a doctor/physician. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. If in eyes, immediately call a POISON CENTER or doctor/physician. Absorb spillage to prevent material damage. Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed. Store the part A component in corrosive resistant container such as polypropylene. Take off contaminated clothing and wash it before reuse. Collect spillage. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

TO FIGHT FIRE:

Solvent may produce excessive pressure during a fire causing sealed containers to rupture and ignite. Cool fire exposed containers with water but do not allow water to enter containers. Fight fire with CO₂, foam, alcohol foam or dry chemical. Fire fighters should wear a self-contained breathing apparatus and full face piece when fighting fire. Hazardous decomposition products may be toxic materials, CO₂, CO, and hydrocarbon compounds etc as well as NO_x, HCN, and other toxic chemicals. Water may react with chemicals when in direct contact.



GARON

GARON PRODUCTS, INC
PO BOX 1924, WALL NJ 07719
1-800-631-5380 - www.garonproducts.com

GARON

HI-GLOSS HIGH SOLIDS™

For Industrial Use Only

**ALIPHATIC URETHANE, HIGH WEAR, TOPCOAT
THREE PART URETHANE**

**MIXING: One pint of part A, 0.70 gallons part B, and a quart container of the aggregate part C (about 3.0 pounds aggregate) and 1 pint color pack component when applying colors. (all volumes and weights approximate)
POT LIFE: 1 gallon volume: 1 to 2 hours @ 70°F.
HIGHER TEMPERATURES & LARGER VOLUMES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.
KEEP OUT OF THE REACH OF CHILDREN

HEALTH: 2 **FLAMMABILITY: 2**
REACTIVITY: 1 **PERSONAL PROTECTION: G**

CHEMICAL CONTENT:

DIPROPYLENE GLYCOL METHYL ETHER ACETATE CAS# 88917-22-0, URETHANE BIS OXAZOLIDINE CAS# 59719-67-4, PROPYLENE CARBONATE CAS# 108-32-7, DIMETHYL PHTHALATE CAS# 131-11-3, DIBUTYLIN DILURATE CAS# 77-58-7, BENZOYL CHLORIDE CAS# 98-88-4, TRIETHYL PHOSPHATE CAS# 78-40-0, Precipitated Silica CAS# 112926-00-8, PENTANEDIONE - 2,4 CAS# 123-54-6, HOMOPOLYMER OF HDI CAS# 28182-81-2, HEXAMETHYLENE DIISOCYANTE (HDI) CAS# 822-06-0, Tabular Alumina CAS# 1344-28-1,

APPLICATION PROCEDURES:

Request and read the technical data sheet before use. See Technical data for surface preparation, mixing instructions and primer information. Pour the mixed material into the application tray. Apply at the rate of 600 square feet per gallon in a uniform manner with a 3/8" nap roller. For uniform appearance, it is critical that the material is not applied above or below this application rate. Dip the roller in the coating and roll out excess material in the roller tray prior to the actual application to the substrate. Overlap subsequent passes being sure no excess material is applied when overlapping. Make sure the floor has just enough material to cover evenly. Finally, re-roll the area in the opposite direction or the first pass applications to level and even the application. As each slab is finished, utilizing spiked shoes, pull the roller across the entire slab without any pressure in one direction and then pull the roller over the slab again overlapping the first pass to remove any roller marks. Remix the material in the application tray to maintain a uniform mix throughout the application process. If the appearance is not satisfactory, re-roll until the area is uniform in appearance. It is almost impossible to over-roll this material. maintain a wet edge to avoid roller marks.

DOT: Part A: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS BENZOYL CHLORIDE), 8, PG II. Part B: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS HEXAMETHYLENE DIISOCYANATE), 9, PG III. Part C: Not Regulated.

IMO/IMDG: Part A: UN2920, CORROSIVE LIQUIDS, FLAMMABLE, N.O.S. (CONTAINS Benzoyl Chloride, DIPROPYLENE GLYCOL METHYL ETHER ACETATE), 8, PG II. Part B: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS HEXAMETHYLENE DIISOCYANATE), 9, PGIII, MARINE POLLUTANT. Part C: Not Regulated.

NOTICE TO BUYER:

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at www.garonproducts.com

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material.

This material has a maximum VOC of 95 grams per liter.