

DANGER!

Harmful in contact with skin. Causes severe skin burns and eye damage. Causes serious eye damage. May cause an allergic skin reaction. May damage the fertility of the unborn child. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapours/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid release to the environment. IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell. Rinse mouth. IF ON SKIN: wash with plenty of soap and water. Call a POISON CENTER or doctor/physician if you feel unwell. Take off immediately all contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If in eyes, immediately call a POISON CENTER or doctor/physician. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. If skin irritation or burns develop, Call a doctor/physician. IF exposed or concerned: Get medical advice/attention. Collect spillage. Store locked up. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

TO FIGHT FIRE:

Fight fire with CO₂, foam, dry chemical or water fog. Hazardous decomposition products may be CO₂, CO, acid, aldehyde and NOX compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.



GARON

GARON PRODUCTS, INC
PO BOX 1924, WALL NJ 07719
1-800-631-5380 - www.garonproducts.com

GARON

JOINT GUARD™

For Industrial Use Only

**JOINT SEALANT
TWO PART**

**MIXING: 8.9# PART A TO 11.3# PART B (BY WEIGHT) ONE PART
A TO ONE PART B (BY VOLUME) (VOLUMES APPROXIMATE)**

**POT LIFE: 2 Gallon Volume: 30 to 40 minutes @ 70°F.
HIGHER TEMPERATURES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.
KEEP OUT OF THE REACH OF CHILDREN

HEALTH: 2 **FLAMMABILITY: 1**
REACTIVITY: 0 **PERSONAL PROTECTION: G**

CHEMICAL CONTENT:

NONYL PHENOL CAS# 84852-15-3, N-AMINOETHYLPIPERAZINE CAS# 140-31-8, *1,2-benzenedicarboxilic acid, dibutyl ester CAS# 84-74-2, LIMESTONE CAS# 1317-65-3, Cellulose CAS# 9004-34-6, Kaolin CAS# 1332-58-7, Talc CAS# 14807-96-6, crystalline silica CAS# 14808-60-7, CARBON CAS# 333-86-4, MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, Alkyl Phenol CAS# 84852-15-3, Alkyl Phenol blocked Isocyanate NJTSRN(31765300002) - 6184P, Cellulose CAS# 9004-34-6, Kaolin CAS# 1332-58-7, Titanium Dioxide CAS# 13463-67-7.

APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Bring material to normal room temperature. Remove any loose concrete or previous joint compound. For best results, edges should be saw cut. Apply material with temperatures between 50-90 degrees F. Mix part A and B together thoroughly using slow speed mixing equipment. If joint is more than 1 1/2" deep, insert a backer rod leaving 1/2" from top of the backer rod. Pour the mixed material slowly into the joint and allow it to settle. It is very important to take the time to mix this material very well. We recommend that at least five minutes be spent in mixing this material. Improper mixing will result in an incomplete cure and soft spots throughout the work area.

DOT: Part A: Not Regulated. Part B: UN1760, CORROSIVE LIQUID N.O.S.

(N-AMINOETHYLPIPERAZINE, DIBUTYL PHTHALATE, NONYL PHENOL), 8, UN1760, PG III, MARINE POLLUTANT.

IMO/IMDG: Part A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PG III, MARINE POLLUTANT. Part B: UN1760, CORROSIVE LIQUID N.O.S. (N-AMINOETHYLPIPERAZINE, DIBUTYL PHTHALATE, NONYL PHENOL), 8, UN1760, PG III, MARINE POLLUTANT.

NOTICE TO BUYER:

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at www.garonproducts.com

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material.

This material has a maximum VOC of zero grams per liter.