

DANGER!

Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Harmful if inhaled. Harmful to aquatic life. Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapours/spray P264 Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Avoid release to the environment. IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell. Rinse mouth. IF ON SKIN: wash with plenty of soap and water. Call a POISON CENTER or doctor/physician if you feel unwell. Take off immediately all contaminated clothing and wash it before reuse. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. If skin irritation or burns develop, Call a doctor/physician. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF SKIN irritation or rash occurs: Get medical advice/attention. If in eyes, immediately call a POISON CENTER or doctor/physician. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Collect spillage. Store locked up. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

TO FIGHT FIRE:

Fight fire with CO2, foam, dry chemical or water fog. Hazardous decomposition products may be CO2, CO and NOX, acids and aldehyde compounds or byproducts. Fire fighters should wear a self-contained breathing apparatus.



GARON

GARON PRODUCTS, INC
PO BOX 1924, WALL NJ 07719
1-800-631-5380 - www.garonproducts.com

GARON

MOISTURE TRAP™

For Industrial Use Only

DAMP FLOOR PRIMER
TWO PART EPOXY

MIXING: 9.25# PART A TO 4.15# PART B

**POT LIFE: 150 gram mass: 28 to 38 minutes @ 70°F.
HIGHER TEMPERATURES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.
KEEP OUT OF THE REACH OF CHILDREN

**HEALTH:
REACTIVITY:** 2
0

**FLAMMABILITY:
PERSONAL PROTECTION:** 1
G

CHEMICAL CONTENT:

Polyoxypropylene diamine CAS# 9046-10-0, 3-Aminomethyl -3,5,5-Trimethyl Cyclohexane CAS# 2855-13-2, Paratertiarybutylphenol CAS# 98-54-4, Benzene-1,3-dimethanamine (MXDA) CAS# 1477-55-0, TRIS-2,4,6-dimethylaminomethylphenol CAS# 90-72-2, BENZYL ALCOHOL CAS# 100-51-6, 2-HYDROXYBENZOIC ACID CAS# 69-72-7, TRIMETHYLHEXAMETHYLENEDIAMINE CAS# 25620-58-0, MODIFIED DIGLICIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, BISPHENOL F/EPICHLOROHYDRIN EPOXY RESIN CAS# 9003-36-5, Glycidoxypropyl trimethoxysilane CAS# 2530-83-8.

APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Properly test, prepare and profile the substrate according to ASTM F3010-13. Remove all contaminants including curing compounds. Make sure the floor surface is dry. Store materials at room temperature before using. Apply material between 60-90 degrees F; lower temperatures will require more time for material to cure. Mix the part A and part B together thoroughly (make sure the mix ratio is correct). Apply the material by brush or roller. Use an air release roller tool to remove entrapped air. After application if necessary, keep the floor dry for seven days (time for the coating to fully cure). Apply with relative humidity below 90% for best results.

DOT: Part A: Not Regulated. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS Polyoxypropylene Diamine, 1,3-Benzenedimethanamine), 8, PG II.

IMO/IMDG: Part A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PG III, MARINE POLLUTANT. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS Polyoxypropylene Diamine, 1,3-Benzenedimethanamine), 8, PG III, MARINE POLLUTANT.

NOTICE TO BUYER:

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at www.garonproducts.com

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. This material has a maximum VOC of 0 grams per liter.