

DANGER!
May Cause cancer. Suspected of damaging fertility of the unborn child. Flammable liquid and vapor. May cause damage to organs through prolonged or repeated exposure. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes severe eye damage. Suspected of causing genetic defects. Harmful if inhaled. Toxic to aquatic life. Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS:
Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/.../equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid release to the environment. In case of fire: Use FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL for extinction. Get medical advice/attention if you feel unwell. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. If skin irritation or burns develop, Call a doctor/physician. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes, immediately call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. Collect spillage. Store locked up. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

TO FIGHT FIRE:
Solvent may produce excessive pressure during a fire causing sealed containers to rupture and ignite. Cool fire exposed containers with water. Fight fire with CO2, foam, alcohol foam or dry chemical. Fire fighters should wear a self-contained breathing apparatus and full face piece when fighting fire. Hazardous decomposition products may be toxic materials, CO2, CO and hydrocarbon compounds, etc. Water may not be effective for fighting fires.



GARON

GARON PRODUCTS, INC
PO BOX 1924, WALL NJ 07719
1-800-631-5380 - www.garonproducts.com

GARON

OIL PRIME™

For Industrial Use Only

**OIL STOP PRIMER
TWO PART EPOXY**

**MIXING: 10.05# PART A TO 8.6# PART B (BY WEIGHT) ONE
PART A TO ONE PART B (BY VOLUME) (VOLUMES APPROXIMATE)**

**POT LIFE: 2 Gallon Volume = 2 to 4 hours @ 70°F.
HIGHER TEMPERATURES & LARGER VOLUMES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.
KEEP OUT OF THE REACH OF CHILDREN

**HEALTH: 3
REACTIVITY: 0** **FLAMMABILITY: 3
PERSONAL PROTECTION: G**

CHEMICAL CONTENT:
PHENOL CAS# 108-95-2, BENZYL ALCOHOL CAS# 100-51-6, HEXANEDIAMINE CAS# 124-09-4, 1,2 CYCLOHEXANEDIAMINE CAS# 694-83-7, Xylene CAS# 1330-20-7, ethyl benzene CAS# 100-41-4, toluene CAS# 108-88-3, NONYL PHENOL CAS# 84852-15-3, Talc CAS# 14807-96-6, crystalline silica CAS# 14808-60-7, TRIS-2,4,6-dimethylaminomethylphenol CAS# 90-72-2, Bis(dimethylaminomethyl) phenol CAS# 71074-89-0, 1,2-Propanediol CAS# 57-55-6, Isobutyl Alcohol CAS# 78-83-1, Salts from alkylamides and esters CAS# Trade secret (NJTSRN 800963-5040), COAL TAR PITCH (Crude Coal Tar) CAS# 65996-89-6, Chrysene CAS# 218-01-9, 1,2-Benzanthracene CAS# 56-55-3, Benzo(a)pyrene CAS# 50-32-8, Benzo(b)Fluoranthene CAS# 205-99-2, Dibenzofuran CAS# 132-64-9, Acenaphthene CAS# 83-32-9, Anthracene CAS# 120-12-7, Fluoranthene CAS# 206-44-0, Phenanthrene CAS# 85-01-8, Naphthalene CAS# 91-20-3, Dibenz (a,h) anthracene CAS# CAS# 53-70-3, , Indeno (1,2,3-cd) pyrene CAS# 193-39-5, Biphenyl CAS# 92-52-4, Reaction Products of Epichlorohydrin-Bisphenol A CAS# 25068-38-6, BUTANOL NORMAL CAS# 71-36-3.

APPLICATION PROCEDURES:
Request and read the technical data sheet before use. Store product at normal room temperature. Make sure the substrate is dry and properly prepared. Remove all contaminants and curing compounds. Apply material between 55-90 degrees F. Colder temperatures will require a longer cure time. Mix part A and part B together thoroughly. Make sure the mix ratio is correct. Always apply a test patch of both this product and topcoat to check suitability. Apply material by brush or roller. Do not use on animal fat, vegetable oil or synthetic oil. Check for epoxy blushes and migrating contamination between coats.
DOT: Part A: UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, BUTANOLS), 3, PG III. Part B: UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, BUTANOLS, COAL TAR), 3, PG III, MARINE POLLUTANT.
IMO/IMDG: Part A: UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, BUTANOLS, Bisphenol A Diglycidyl Ether Polymer), 3, PG III, MARINE POLLUTANT. Part B: UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, BUTANOLS, COAL TAR), 3, PG III, MARINE POLLUTANT.

NOTICE TO BUYER:
Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at www.garonproducts.com
Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material.
This material has a maximum VOC of 330 grams per liter.