

**DANGER!**

May cause cancer. Causes damage to organs through prolonged or repeated exposures (lungs, respiratory system). May cause respiratory irritation. Combustible liquids. Harmful if swallowed. Harmful in contact with skin. Causes serious eye damage. May cause an allergic skin reaction. Causes severe skin burns and eye damage. Suspected of damaging fertility of the unborn child.

Toxic to aquatic life

**PRECAUTIONARY STATEMENTS:**

Keep out of reach of children. Read label before use. Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Wear protective

gloves/protective clothing/eye protection/face protection. IF SWALLOWED: call a POISON

CENTER or doctor/physician IF you feel unwell. Rinse mouth. IF ON SKIN: wash with plenty

of soap and water. Call a POISON CENTER or doctor/physician if you feel unwell. Take off

immediately all contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. If in eyes, immediately call a POISON CENTER or doctor/physician.

IF SKIN irritation or rash occurs: Get medical advice/attention. Dispose of

contents/container to a waste disposal facility in accordance with local, state, federal or

international laws.

**TO FIGHT FIRE:**

Fight fire with CO<sub>2</sub>, foam, dry chemical or water fog. Hazardous decomposition products

may be CO<sub>2</sub>, CO and NO<sub>x</sub> compounds or by-products. Fire fighters should wear a

self-contained breathing apparatus.



# GARON

GARON PRODUCTS, INC  
PO BOX 1924, WALL NJ 07719  
1-800-631-5380 - [www.garonproducts.com](http://www.garonproducts.com)

# GARON

## POUR-N-WALK™

For Industrial Use Only

### SELF LEVELING RESURFACER TWO PART EPOXY PLUS AGGREGATE

**MIXING: 9.65# PART A TO 4.5# PART B +20# MIXED AGGREGATE TWO PARTS A TO ONE PART B (BY VOLUME) (VOLUMES APPROXIMATE)**

**POT LIFE: 1.5 Gallon Volume: 2 to 3 hours @ 70° F.  
HIGHER TEMPERATURES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.  
**KEEP OUT OF THE REACH OF CHILDREN**

**HEALTH:  
REACTIVITY:** 2  
0

**FLAMMABILITY:  
PERSONAL PROTECTION:** 1  
G

**CHEMICAL CONTENT:**

AMINO TERMINATED POLYETHER CAS# 9046-10-0, BENZYL ALCOHOL CAS# 100-51-6, 1,2-CYCLOHEXANEDIAMINE CAS# 694-83-7, TRIS-2,4,6-dimethylaminomethylphenol CAS# 90-72-2, Bis(dimethylaminomethyl) phenol CAS# 71074-89-0, NONYL PHENOL CAS# 84852-15-3, N-AMINOETHYLPIPERAZINE CAS# 140-31-8, 1-Methoxy-2-Propanol Acetate CAS# 108-65-6, Naphtha-Light Aromatic CAS# 64742-95-6, Additive NJTSRN: 800963-5061, 1,2,4-trimethylbenzene CAS# 95-63-6, 2, 6-Dimethyl-4-Heptanone CAS# 108-83-8, 4,6-Dimethyl-2-heptanone CAS# 19549-80-5, solution of polyacrylate CAS# trade secret (NJTSRN 800963-549), SILICON DIOXIDE CAS# 14808-60-7, MODIFIED DIGLYCIDYL ETHER OF BISPENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, Xylene CAS# 1330-20-7, 2,6-Dimethyl-4-Heptanone CAS# 108-83-8, Ethyl benzene CAS# 100-41-4, Butyl Acetate CAS# 123-86-4, 1,2-Propanediol CAS# 57-55-6, Isobutyl Alcohol CAS# 78-83-1, Salts from alkylamides and esters CAS# Trade secret (NJTSRN 800963-5040), COLORS MAY CONTAIN: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4, Precipitated Silica CAS# 112926-00-8, Iron III hydroxide CAS# 20344-49-4, Yellow Pigment CAS# not available, Zinc Sulfide (component of yellow pigment) CAS# 1314-98-3, Barium Sulfate (component of yellow pigment) CAS# 7727-43-7, Pigment yellow 65 (component of yellow pigment) CAS# 6528-34-3, Iron III oxide CAS# 20344-49-4, C.I. Pigment Blue CAS# 147-14-8, Aluminum Oxide CAS# 1344-28-1, silica, amorphous CAS# 7631-86-9, Iron Oxide Yellow CAS# 51274-00-1, Silica, amorphous CAS# 7631-86-9.

**APPLICATION PROCEDURES:**

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the floor surface is dry. Store material at room temperature before using. Apply an appropriate primer. Apply material between 60-90 degrees F with relative humidity below 85% (if R.H. is above 70%, let the material induct for 5-15 min.). Mix part A and part B together then add in the provided aggregate (mix occasionally to insure the aggregate does not settle out). Apply with a notched squeegee and back roll with a roller. Use an air release roller tool to remove entrapped air. When topcoating, check for epoxy blushes before recoating and lightly roughen the surface to insure bonding.

**DOT:** Part A: NA1993, COMBUSTIBLE LIQUID N.O.S. (CONTAINS XYLENE, ISOBUTYL ALCOHOL), 3, PG III.

Part B: UN1760, CORROSIVE LIQUID N.O.S. (N-AMINOETHYLPIPERAZINE, 1,2-CYCLOHEXANEDIAMINE), 8, PG III.

Part C: Not Regulated.

**IMO/IMDG:** Part A: UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, ISOBUTYL ALCOHOL, Bisphenol A Diglycidyl Ether Polymer), 3, PG III, marine pollutant. Part B: UN1760, CORROSIVE LIQUID N.O.S. (N-AMINOETHYLPIPERAZINE, 1,2-CYCLOHEXANEDIAMINE, NONYL PHENOL), 8, PG III, MARINE POLLUTANT.

**NOTICE TO BUYER:**

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at [www.garonproducts.com](http://www.garonproducts.com). Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material.

This material has a maximum VOC of 15 grams per liter.