

**DANGER!**

May cause cancer. Causes damage to organs through prolonged or repeated exposures (lungs, respiratory system). May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Causes Severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS:**

Keep out of reach of children. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Read label before use. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. Get medical advice/attention if you feel unwell. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. If skin irritation or burns develop, Call a doctor/physician. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If in eyes, immediately call a POISON CENTER or doctor/physician. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Collect spillage.

Disposal: Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

**TO FIGHT FIRE:**

Fight fire with CO<sub>2</sub>, foam, dry chemical or water fog. Hazardous decomposition products may be CO<sub>2</sub>, CO, acids, aldehyde and NOX compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.



# GARON

GARON PRODUCTS, INC  
PO BOX 1924, WALL NJ 07719  
1-800-631-5380 - [www.garonproducts.com](http://www.garonproducts.com)

# GARON

## POUR-N-WALK CR™

For Industrial Use Only

### NOVOLAC SELF LEVELER TWO PART EPOXY PLUS AGGREGATE

**MIXING: 10.15# PART A TO 4.2# PART B AND 15# AGGREGATE TWO PARTS A TO ONE PART B (BY VOLUME) (VOLUMES APPROXIMATE)**

**POT LIFE: 1.5 Gallon Volume: 25-35 minutes @ 70°F  
HIGHER TEMPERATURES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.  
**KEEP OUT OF THE REACH OF CHILDREN**

**HEALTH: 2**  
**REACTIVITY: 0**  
**FLAMMABILITY: 1**  
**PERSONAL PROTECTION: G**

**CHEMICAL CONTENT:**

SILICON DIOXIDE CAS# 14808-60-7, BENZYL ALCOHOL CAS# 100-51-6, METHYLENEDI (CYCLOHEXYLAMINE) CAS# 1761-71-3, cyclohexanamine, 4,4-methylenebis reaction products CAS# 129733-57-9, 3-AMINOMETHYL-3,5,5-TRIMETHYL CYCLOHEXANE CAS# 2855-13-2, 2-HYDROXYBENZOIC ACID CAS# 69-72-7, MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, Epoxy phenol novolac resin CAS# 28064-14-4, BISPHENOL F/EPICHLOROHYDRIN EPOXY RESIN CAS# 9003-36-5, PROPYLENE GLYCOL MONOMETHYL ETHER CAS# 107-98-2, Siloxanes and silicones, di-me reactions products with silica CAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9, STODDARD SOLVENT CAS# 8052-41-3, 1-Methoxy-2-Propanol Acetate CAS# 108-65-6, 1,2,4-Trimethylbenzene CAS# 95-63-6, sec-butyl alcohol CAS# 78-92-2, acetic acid, butyl ester CAS# 123-86-4, COLORS MAY CONTAIN: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4, Precipitated Silica CAS# 112926-00-8, Iron III oxide CAS# 1309-37-1, Zinc Sulfate CAS# 1314-98-3, Barium Sulfate CAS# 7727-43-7, Pigment yellow 65 CAS# 6528-34-3, Iron III oxide CAS# 20344-49-4, C.I. Pigment Blue CAS# 147-14-8, Aluminum Oxide CAS# 1344-28-1, Silica, amorphous CAS# 7631-86-9, Iron Oxide Yellow CAS# 51274-00-1, Silica amorphous CAS# 7631-86-9.

**APPLICATION PROCEDURES:**

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the floor surface is dry. Store material at room temperature before using. Apply an appropriate primer. Apply material between 60-90 degrees F with relative humidity below 90% for best results. Make sure the correct weight of each component is used. Mix part A and part B together, then add in the aggregate (mix occasionally to insure the aggregate does not settle out). Apply with a notched squeegee and back roll with a roller. Use an air release roller tool to remove entrapped air. When topcoating, check for epoxy blushes before recoating and lightly roughen the surface to insure bonding.

**DOT:** Part A: Not Regulated. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, 2-HYDROXY BENZOIC ACID), 8, PG III. Part C: Not Regulated.

**IMO/IMDG:** Part A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PGIII, MARINE POLLUTANT. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, 2-HYDROXY BENZOIC ACID, BENZYL ALCOHOL), 8, PG III, MARINE POLLUTANT. Part C: Not Regulated.

**NOTICE TO BUYER:**

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at [www.garonproducts.com](http://www.garonproducts.com)

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. This material has a maximum VOC of 22 grams per liter.