

**WARNING!**

Causes skin irritation. May cause an allergic skin reaction. Causes eye irritation. Harmful if inhaled. Harmful if swallowed. Toxic to aquatic life with long lasting effects

**PRECAUTIONARY STATEMENTS:**

Keep out of reach of children. Read label before use. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Avoid release to the environment. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice/attention. IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell. Rinse mouth. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Collect spillage. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

**TO FIGHT FIRE:**

Fight fire with CO<sub>2</sub>, foam, dry chemical or water fog. Hazardous decomposition products may be CO<sub>2</sub>, CO, acid, aldehyde and NOX compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.



**GARON**

GARON PRODUCTS, INC  
PO BOX 1924, WALL NJ 07719  
1-800-631-5380 - [www.garonproducts.com](http://www.garonproducts.com)

**GARON**

**POXYPASTE™**

For Industrial Use Only

**CRACK FILLER  
TWO PART EPOXY**

**MIXING: 11.1# PART A TO 11.2# PART B (BY WEIGHT) ONE  
PART A TO ONE PART B (BY VOLUME) (VOLUMES APPROXIMATE)**

**POT LIFE: 2 Gallon Volume = 1 to 3 hours @ 70°F.  
HIGHER TEMPERATURES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.  
**KEEP OUT OF THE REACH OF CHILDREN**

**HEALTH: 2**      **FLAMMABILITY: 1**  
**REACTIVITY: 0**      **PERSONAL PROTECTION: G**

**CHEMICAL CONTENT:**

TRIETHYLENE TETRAMINE CAS# 112-24-3, Dimer/tofa, reaction products with Teta CAS# 68082-29-1, HYDROCARBON RESIN - NON-HAZARDOUS, Naphthalene CAS# 91-20-3, HYDROXY MODIFIED RESIN - NON-HAZARDOUS, Xylene CAS# 1330-20-7, ethyl benzene CAS# 100-41-4, Alky Quaternary Ammonium Bentonite CAS# 68953-58-2, crystalline silica CAS# 14807-60-7, Talc CAS# 14807-96-6, LIMESTONE CAS# 1317-65-3, BENZYL ALCOHOL CAS# 100-51-6, CARBON CAS# 1333-86-4, Titanium Dioxide CAS# 13463-67-7, MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6.

**APPLICATION PROCEDURES:**

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the surface is dry. Store at room temperature before using. Apply material with temperatures between 60-90 degrees F. Mix the material at the correct mix ratio using a putty knife until streak free and uniform in appearance. Make sure all loose concrete is removed prior to filling any cracks. Apply the material with a putty knife or other suitable application tool. Most coatings can be applied directly over the uncured crack filler provided the repairs are shallow and narrow. For larger repairs, allow the material to fully cure before applying a coating.

**DOT:** Part A: Not Regulated. Part B: Not Regulated.

**IMO/IMDG:** Part A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PG III, MARINE POLLUTANT. Part B: Not Regulated.

**NOTICE TO BUYER:**

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at [www.garonproducts.com](http://www.garonproducts.com). Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. This material has a maximum VOC of 11 grams per liter.