

**DANGER!**

Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life. Toxic to aquatic life with long lasting effects

**PRECAUTIONARY STATEMENTS:**

Keep out of reach of children. Read label before use. Do not breathe dust/fume/gas/mist/vapours/spray P264 Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. If skin irritation or burns develop, Call a doctor/physician . If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If in eyes, immediately call a POISON CENTER or doctor/physician. Store locked up. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

**TO FIGHT FIRE:**

Fight fire with CO2, foam, dry chemical or water fog. Hazardous decomposition products may be CO2, CO, acid, aldehyde and NOX compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.



**GARON**

GARON PRODUCTS, INC  
PO BOX 1924, WALL NJ 07719  
1-800-631-5380 - [www.garonproducts.com](http://www.garonproducts.com)

**GARON**

**STOP SLIP HDV™**

For Industrial Use Only

TEXTURED NON-SLIP COATING  
TWO PART EPOXY

**MIXING: 10.05# PART A TO 1.90# PART B**

**POT LIFE: 1 Gallon Volume: 1 hours @ 70°F  
HIGHER TEMPERATURES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.  
**KEEP OUT OF THE REACH OF CHILDREN**

**HEALTH: 2**      **FLAMMABILITY: 1**  
**REACTIVITY: 0**      **PERSONAL PROTECTION: G**

**CHEMICAL CONTENT:**

BENZYL ALCOHOL CAS# 100-51-6, 3-AMINOMETHYL-3,5,5-TRIMETHYL CYCLOHEXANE CAS# 2855-13-2, 2-HYDROXYBENZOIC ACID CAS# 69-72-7, Precipitated Silica CAS# 112926-00-8, Hydrophobic Silica CAS# 67762-90-7, MODIFIED DIGLYCIDYL ETHER OF BISPENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, STODDARD SOLVENT CAS# 8052-41-3, 1-Methoxy-2-Propanol Acetate CAS# 108-65-6, 1,2,4-Trimethylbenzene CAS# 95-63-6, Solvent naphtha, petroleum, heavy aromatic CAS# 64742-94-5, Hydrophobic Silica CAS# 67762-90-7, Poly(terephthaloylchloride/P-phenylenediamine) CAS#26125-61-1, Sodium Sulphate CAS# 7757-82-6, ALUMINUM OXIDE CAS# 1344-28-1, SILICON DIOXIDE CAS# 14808-60-7, Colors may contain: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4, Precipitated Silica CAS# 112926-00-8, Iron III oxide CAS# 1309-37-1, Yellow Pigment CAS# Not available, Zinc Sulfide CAS# 1314-98-3, Barium Sulfate CAS# 7727-43-7, Pigment yellow 65 CAS# 6528-34-3, Iron III hydroxide CAS# 20344-49-4, C.I. Pigment Blue CAS# 147-14-8, Aluminum Oxide CAS# 1344-28-1, Silica, amorphous CAS# 7631-86-9, Iron Oxide Yellow CAS# 51274-00-1.

**APPLICATION PROCEDURES:**

Request and read the technical data sheet before use. Store material at normal room temperature before using. Make certain that the surface is clean and dry. Mix material with slow speed mixing equipment until streak free and thoroughly mixed. Apply material with temperatures between 55-90 degrees F and relative humidity below 90%. Make sure the mix ratio is correct before applying material. Apply the mixed material with a phenolic core applicator rolling out the material uniformly and in one direction to align the peaks and valleys generated from the application. It is best to pour out a ribbon of material on the surface about 6 inches wide and then pull the material toward you with moderate pressure. Do not over-roll.

**DOT:** Part A: Not Regulated. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE), 8, PG III.

**IMO/IMDG:** Part A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PG III. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, BENZYL ALCOHOL), 8, PG III, Marine Pollutant.

**NOTICE TO BUYER:**

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at [www.garonproducts.com](http://www.garonproducts.com)

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. This material has a maximum VOC of 2 grams per liter.