

DANGER!

Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Flammable liquid and vapor. May cause damage to organs (auditory system) through prolonged or repeated exposure. May cause drowsiness or dizziness. May be harmful if swallowed and enters airways. Harmful in contact with skin. May cause an allergic skin reaction. Harmful if inhaled. Harmful to aquatic life. Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Do not breathe dust/fume/gas/mist/vapours/spray P264 Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/.../equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Avoid release to the environment. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. If skin irritation or burns develop, Call a doctor/physician. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If in eyes, immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. In case of fire: Use FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL for extinction. Get medical advice/attention if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Do NOT induce vomiting. IF ON SKIN: wash with plenty of soap and water. Take off immediately all contaminated clothing and wash it before reuse. IF SKIN irritation or rash occurs: Get medical advice/attention. IF eye irritation persists: Get medical advice/attention.

Avoid release to the environment. Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

TO FIGHT FIRE:

Solvent may produce excessive pressure during a fire causing sealed containers to rupture and ignite. Cool fire exposed containers with water. Fight fire with CO2, foam, alcohol foam or dry chemical. Fire fighters should wear a self-contained breathing apparatus and full face piece when fighting fire. Hazardous decomposition products may be toxic materials, carbon dioxide, carbon monoxide, NOX compounds etc. Water may not be effective for fighting fires.



GARON

GARON PRODUCTS, INC
PO BOX 1924, WALL NJ 07719
1-800-631-5380 - www.garonproducts.com

GARON

STOP SLIP HD™

For Industrial Use Only

TEXTURED NON-SLIP COATING
TWO PART EPOXY

MIXING: 12.15# PART A TO 1.25# PART B

**POT LIFE: 1 Gallon Volume: 1.5 hours @ 70°F
HIGHER TEMPERATURES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.
KEEP OUT OF THE REACH OF CHILDREN

**HEALTH:
REACTIVITY: 2
0**

**FLAMMABILITY: 2
PERSONAL PROTECTION: G**

CHEMICAL CONTENT:

BENZYL ALCOHOL CAS# 100-51-6, 3-AMINOMETHYL-3,5,5-TRIMETHYL CYCLOHEXANE CAS# 2855-13-2, 2-HYDROXYBENZOIC ACID CAS# 69-72-7, Precipitated Silica CAS# 112926-00-8, MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, STODDARD SOLVENT CAS# 8052-41-3, 1-Methoxy-2-Propanol Acetate CAS# 108-65-6, 1,2,4-Trimethylbenzene CAS# 95-63-6, Solvent naphtha, petroleum, heavy aromatic CAS# 64742-94-5, Hydrophobic Silica CAS# 67762-90-7, Poly(terephthaloylchloride/P-phenylenediamine) CAS#26125-61-1, Sodium Sulphate CAS# 7757-82-6, Xylene CAS# 1330-20-7, ethyl benzene CAS# 100-41-4, toluene CAS# 108-88-3, ALUMINUM OXIDE CAS# 1344-28-1, SILICON DIOXIDE CAS# 14808-60-7, Attapulgitte clay CAS# 12174-11-7,), Colors may contain: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4, Precipitated Silica CAS# 112926-00-8, Iron III oxide CAS# 1309-37-1, Yellow Pigment CAS# Not available, Zinc Sulfide CAS# 1314-98-3, Barium Sulfate CAS# 7727-43-7, Pigment yellow 65 CAS# 6528-34-3, Iron III hydroxide CAS# 20344-49-4, C.I. Pigment Blue CAS# 147-14-8, Aluminum Oxide CAS# 1344-28-1, Silica, amorphous CAS# 7631-86-9, Iron Oxide Yellow CAS# 51274-00-1.

APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Store product at room temperature. Make sure the surface is dry and free of all curing compounds, grease, oil and dirt. Apply with temperature between 55-90F and R.H. below 90%. Mix material well before using. Apply by pouring a ribbon of material on surface 6 inches wide; then pull the material in one direction using a phenolic core applicator tool with a moderate amount of pressure. Do not over roll too many times and do not apply excessive pressure downward. Apply by pulling material in only one direction. Read the technical data for more in depth application details.

DOT: Part A: NA1993, COMBUSTIBLE LIQUID N.O.S. (ETHYL BENZENE, XYLENE), 3, PG III. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE), 8, PG III. **IMO/IMDG:** Part A: UN1993, FLAMMABLE LIQUID N.O.S. (ETHYL BENZENE, XYLENE, MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A), 3, PG III, MARINE POLLUTANT. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, BENZYL ALCOHOL), 8, PG III, Marine Pollutant.

NOTICE TO BUYER:

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at www.garonproducts.com

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. This material has a maximum VOC of 2 grams per liter.