

WARNING!

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Harmful to aquatic life.

PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Wear protective gloves/protective clothing/eye protection/face protection. Wash skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice/attention. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

TO FIGHT FIRE:

FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG. DO NOT ENTER CONFINED AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS.



GARON

GARON PRODUCTS, INC
PO BOX 1924, WALL NJ 07719
1-800-631-5380 - www.garonproducts.com

GARON

TIGERCLEAN CTR™

For Industrial Use Only

CLEANER

MIXING: For heavy duty cleaning and degreasing, we recommend 1 part cleaner concentrate to 4 parts water by volume. Deviations from this ratio can accommodate differing concentration suited to the cleaning strength needed. For less soiled floors, dilute with more water and for heavily soiled floors, dilute with less water. Ratios varying from 1:1 to 50:1 (Water to cleaner concentrate) can be used for general cleaning.

POT LIFE:

HIGHER TEMPERATURES & LARGER VOLUMES DECREASE POT LIFE

Lot Number:

Read carefully other cautions on side panel.
KEEP OUT OF THE REACH OF CHILDREN

HEALTH: 1 **FLAMMABILITY: 0**
REACTIVITY: 0 **PERSONAL PROTECTION: G**

CHEMICAL CONTENT:

NONYLPHENOXYPOLYETHOXYETHANOL CAS# 68412-54-4,
N-METHYL-2-PYRROLIDONE CAS# 872-50-4, WATER CAS# 7732-18-5,
MONOCYCLIC TERPENE HYDROCARBONS CAS# 94266-47-4, TRIETHANOLAMINE
(ALKANOLAMINE) CAS# 102-71-6, C.I. Acid Blue 9 CAS# 3844-45-9.

APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Dilute product to the desired strength and apply to the surface with a mopping action. Allow the solution to remain on the floor for approximately 2-5 minutes if the floor is heavily soiled. Remove loosened grime and dirt by mopping and then rinse the floor with clean water. Hot tank application procedures: dilute product with water at the ratio of 1:10 for heavy duty cleaning and 1:20 for light duty cleaning. After determining the size of the tank and agitate the material until thoroughly mixed. Heat the solution from between 125 to 150 degrees F. Immerse the parts to be cleaned into the solution. After the soil is removed from the parts, remove the parts and allow them to air dry. This product contains a short term rust inhibitor, therefore, do not expose metal parts to the cleaning solution for lengthy periods of time. For industrial and commercial use only. Keep out of the reach of children. Read the MSDS prior to using this product.

DOT: Not Regulated.

IMO/IMDG: Not Regulated.

NOTICE TO BUYER:

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at www.garonproducts.com
Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. his material has a maximum VOC of 39.54 gram per liter (282.5g/l regulatory)