

**DANGER!**

Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure (skin, central nervous system (CNS)).

Harmful if swallowed. Harmful in contact with skin. Causes serious eye damage. May cause an allergic skin reaction. Causes severe skin burns and eye damage. Suspected of damaging fertility of the unborn child.

Toxic to aquatic life

**PRECAUTIONARY STATEMENTS:**

Keep out of reach of children. Read label before use. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves and clothing to prevent skin contact. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid release to the environment. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Get medical advice/attention if you feel unwell. IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell. IF ON SKIN: wash with plenty of soap and water. Take off immediately all contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If in eyes, immediately call a POISON CENTER or doctor/physician.

IF SKIN irritation or rash occurs: Get medical advice/attention. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. Wash contaminated clothing before reuse. If skin irritation or burns develop, Call a doctor/physician. IF exposed or concerned: Get medical advice/attention. Store locked up. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

**TO FIGHT FIRE:**

Fight fire with CO<sub>2</sub>, foam, dry chemical or water fog. Hazardous decomposition products may be CO<sub>2</sub>, CO, acids, aldehyde and NO<sub>x</sub> compounds or byproducts. Fire fighters should wear a self-contained breathing apparatus.



**GARON**

GARON PRODUCTS, INC  
PO BOX 1924, WALL NJ 07719  
1-800-631-5380 - [www.garonproducts.com](http://www.garonproducts.com)

**GARON**

**TIGERFLEX™**

For Industrial Use Only

FLEXIBLE COATING  
TWO PART EPOXY

**MIXING: 9.2# PART A TO 8.2# PART B (BY WEIGHT) 1 PART A TO 1 PART B (BY VOLUME) (VOLUMES APPROXIMATE)**

**POT LIFE: 2 Gallon Volume: 15 to 25 minutes @ 70°F.**

**HIGHER TEMPERATURES & LARGER VOLUMES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.  
**KEEP OUT OF THE REACH OF CHILDREN**

**HEALTH:  
REACTIVITY: 2  
0**

**FLAMMABILITY: 1  
PERSONAL PROTECTION: G**

**CHEMICAL CONTENT:**

METHYLENEDI(CYCLOHEXYLAMINE) CAS# 1761-71-3, NONYL PHENOL CAS# 84852-15-3, ALIPHATIC POLYAMINE NJTSRN 05995500-H2390U, MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, additive NJTSRN 800963-5023), Siloxanes and silicones, di-me reactions products with silica CAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9.

**APPLICATION PROCEDURES:**

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the floor surface is dry. Store all material at room temperature before using. Repair large joints and cracks. Apply material between 60-90 degrees F-lower temperatures will require more time for material to cure. Check preceding coats for blushes before recoating. Mix the part A and part B together thoroughly (make sure the mix ratio is correct). Apply the material by brush or roller. After the material is applied, broadcast with aggregate while wet and before recoating.

**DOT:** Part A: Not Regulated. Part B: UN1760, CORROSIVE LIQUID N.O.S. (NONYL PHENOL, METHYLENEDI(CYCLOHEXYLAMINE)), 8, PG III.

**IMO/IMDG:** Part A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer) , 9, PGII, MARINE POLLUTANT. Part B: UN1760, CORROSIVE LIQUID N.O.S. (NONYL PHENOL, METHYLENEDI(CYCLOHEXYLAMINE)), 8, PG III, MARINE POLLUTANT.

**NOTICE TO BUYER:**

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at [www.garonproducts.com](http://www.garonproducts.com). Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. This material has a maximum VOC of zero gram per liter.