

DANGER!

May cause cancer. Causes damage to organs through prolonged or repeated exposures (lungs, respiratory system). May cause respiratory irritation. Harmful if swallowed. May cause damage to organs (kidneys, liver, pancreas and spleen, and edema to the lungs) through inhalation and skin absorption. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Harmful if inhaled. Suspected of causing genetic defects. Harmful in contact with skin. Toxic to aquatic life.

Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid release to the environment. Get medical advice/attention if you feel unwell. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. If skin irritation or burns develop, Call a doctor/physician. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off immediately all contaminated clothing and wash it before reuse. If in eyes, immediately call a POISON CENTER or doctor/physician. If inhaled, Call a POISON CENTER or doctor/physician if you feel unwell. IF exposed or concerned: Get medical advice/attention. Collect spillage. Store locked up. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

TO FIGHT FIRE:
Fight fire with CO2, foam, dry chemical or water fog. Hazardous decomposition products may be CO2, CO, acids, aldehyde and NOX compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.



GARON

GARON PRODUCTS, INC
PO BOX 1924, WALL NJ 07719
1-800-631-5380 - www.garonproducts.com

GARON

TIGERFREEZE™

For Industrial Use Only

**FREEZER FORMULATION
THREE PART MORTAR**

**MIXING: 6.25# PART A TO 2.3125# PART B AND
AGGREGATE**

POT LIFE: .45 cu. Ft. mix: 10 to 15 minutes @ 70°F.

HIGHER TEMPERATURES & LARGER VOLUMES DECREASE POT LIFE

Lot Number:

Read carefully other cautions on side panel.
KEEP OUT OF THE REACH OF CHILDREN

**HEALTH:
REACTIVITY: 3
0**

**FLAMMABILITY: 1
PERSONAL PROTECTION: G**

CHEMICAL CONTENT:

SILICON DIOXIDE CAS# 14808-60-7, PHENOL CAS# 108-95-2, M-XYLENE DIAMINE CAS# 1477-55-0, Benzene-1, 3-Dimethanamine/ Phenol/Formaldehyde CAS# 57214-10-5, MODIFIED DIGLYCIDYL ETHER OF BISPENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, Benzyl Alcohol CAS# 100-51-6, Colors may contain: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4, Precipitated Silica CAS# 112926-00-8, Iron III oxide CAS# 1309-37-1, Yellow Pigment CAS# Not available, Zinc Sulfide CAS# 1314-98-3, Barium Sulfate CAS# 7727-43-7, Pigment yellow 65 CAS# 6528-34-3, Iron III hydroxide CAS# 20344-49-4, C.I. Pigment Blue CAS# 147-14-8, Aluminum Oxide CAS# 1344-28-1, Silica, amorphous CAS# 7631-86-9, Iron Oxide Yellow CAS# 51274-00-1

APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the floor is dry. Store materials at normal room temperature prior to using. Apply material between 30-80 degrees F. Product can be applied without a primer. Note: This product has a very short pot life, working time may be as little as 10-15 minutes once mixed. Mix the part A and part B together thoroughly (be certain the mix ratio is correct). After the part A and part B are mixed, add in the aggregate.

Thoroughly mix to make sure all of the aggregate is wetted out properly. Apply the mixed mortar at the recommended thickness using a hand trowel or other suitable equipment.

DOT: Part A: Not Regulated. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS PHENOL SOLUTIONS, M-XYLENE DIAMINE), 8, PG III. Part C: Not Regulated

IMO/IMDG: Part A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PGIII, MARINE POLLUTANT. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS PHENOL SOLUTIONS, M-XYLENE DIAMINE), 8, PG III, MARINE POLLUTANT. Part C: Not Regulated.

NOTICE TO BUYER:

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at www.garonproducts.com

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material.

This material has a maximum VOC of zero grams per liter.