

DANGER!

Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life. Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. If skin irritation or burns develop, Call a doctor/physician. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If in eyes, immediately call a POISON CENTER or doctor/physician.

Store locked up. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

TO FIGHT FIRE:

Fight fire with CO2, foam, dry chemical or water fog. Hazardous decomposition products may be CO2, CO, acids, aldehydes and NOX compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.



GARON

GARON PRODUCTS, INC
PO BOX 1924, WALL NJ 07719
1-800-631-5380 - www.garonproducts.com

GARON

TIGERSHIELD™

For Industrial Use Only

**HIGH PERFORMANCE
TWO PART EPOXY**

**MIXING: 9.55# PART A TO 4.2# PART B (BY WEIGHT) TWO PARTS
A TO ONE PART B (BY VOLUME) (VOLUMES APPROXIMATE)**

**POT LIFE: 1.5 Gallon Volume: 23-33 minutes @ 70°F.
HIGHER TEMPERATURES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.
KEEP OUT OF THE REACH OF CHILDREN

HEALTH: 2 **FLAMMABILITY: 1**
REACTIVITY: 0 **PERSONAL PROTECTION: G**

CHEMICAL CONTENT:

BENZYL ALCOHOL CAS# 100-51-6, 3-AMINOMETHYL-3,5,5-TRIMETHYL CYCLOHEXANE CAS# 2855-13-2, 2-HYDROXYBENZOIC ACID CAS# 69-72-7, Precipitated Silica CAS# 112926-00-8, REACTION PRODUCTS OF EPICHLOROHYDRIN BISPHENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, STODDARD SOLVENT CAS# 8052-41-3, 1-Methoxy-2-Propanol Acetate CAS# 108-65-6, 1,2,4-Trimethylbenzene CAS# 95-63-6, PROPYLENE GLYCOL MONOMETHYL ETHER CAS# 107-98-2, Solvent naphtha, petroleum, heavy aromatic CAS# 64742-94-5, Siloxanes and silicones, di-me reactions products with silica CAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9, Colors May Contain: Titanium Dioxide CAS# 13463-67-7, Carbon black CAS# 1333-86-4, Precipitated Silica CAS# 112926-00-8, Iron III oxide CAS# 1309-37-1, Yellow Pigment CAS# Not available, Zinc Sulfide (component of yellow pigment) CAS# 1314-98-3, Barium Sulfate (component of yellow pigment) CAS# 7727-43-7, Pigment yellow 65 (component of yellow pigment) CAS# 6528-34-3, Iron III hydroxide CAS# 20344-49-4, C.I. Pigment Blue CAS# 147-14-8, Aluminum Oxide CAS# 1344-28-1, Silica, amorphous CAS# 7631-86-9, Iron Oxide Yellow CAS# 51274-00-1

APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the floor surface is dry. Store all material at room temperature before using. Apply an appropriate primer. Apply material between 50-90 degrees F. Mix part A and part B together thoroughly (make sure that the mix ratio is correct). Apply the material by brush or roller at the recommended thickness. Use an air release roller tool to remove any entrapped air prior to the coating tacking off. Always check the preceding coat and subsequent topcoats for foreign contaminants or epoxy blushes prior to proceeding. Product is temperature sensitive, when temperatures are lower, the material will take more time to cure. For best results, apply material with relative humidity below 85%.

DOT: PART A: Not Regulated PART B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE), 8, PG III

IMO/IMDG: PART A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PGIII, MARINE POLLUTANT PART B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, BENZYL ALCOHOL), 8, PG III, Marine Pollutant

NOTICE TO BUYER:

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at www.garonproducts.com

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. This material has a maximum VOC of 34 grams per liter.