

**DANGER!**

Harmful if swallowed. Harmful in contact with skin. Causes serious eye damage. May cause an allergic skin reaction. Causes severe skin burns and eye damage. Suspected of damaging fertility of the unborn child.

Toxic to aquatic life

**PRECAUTIONARY STATEMENTS:**

Keep out of reach of children. Read label before use. IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell. Rinse mouth. IF ON SKIN: wash with plenty of soap and water. Call a POISON CENTER or doctor/physician if you feel unwell. Take off immediately all contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If in eyes, immediately call a POISON CENTER or doctor/physician. IF SKIN irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

Store locked up. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

**TO FIGHT FIRE:**

Fight fire with CO<sub>2</sub>, foam, dry chemical or water fog. Hazardous decomposition products may be CO<sub>2</sub>, CO, acids, aldehydes and NOX compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.



**GARON**

GARON PRODUCTS, INC  
PO BOX 1924, WALL NJ 07719  
1-800-631-5380 - [www.garonproducts.com](http://www.garonproducts.com)

**GARON**

**TIGERWALL™**

For Industrial Use Only

WATER BASED, WALL COATING  
TWO PART EPOXY

**MIXING: 8.9# PART A TO 1.6# PART B**

**POT LIFE: 1 Gallon Volume: 45-90 minutes @ 70°F.  
HIGHER TEMPERATURES & LARGER VOLUMES DECREASE POT LIFE**

Lot Number:

Read carefully other cautions on side panel.  
**KEEP OUT OF THE REACH OF CHILDREN**

**HEALTH: 2**      **FLAMMABILITY: 1**  
**REACTIVITY: 0**      **PERSONAL PROTECTION: G**

**CHEMICAL CONTENT:**

3-AMINOMETHYL-3,5,5-TRIMETHYL CYCLOHEXANE CAS# 2855-13-2, NONYL PHENOL CAS# 84852-15-3, AMINO TERMINATED POLYETHER CAS# 9046-10-0, Hydrophobic Silica CAS# 67762-90-7, MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, ALKYL GLYCIDYL ETHER CAS# 68609-97-2, Talc CAS# 14807-96-6, crystalline silica CAS# 14808-60-7, LIMESTONE CAS# 1317-65-3, XYLENE CAS# 1330-20-7, ethyl benzene CAS# 100-41-4, Siloxanes and silicones, di-me reactions products with silica CAS# 67762-90-7, siloxanes and silicones, di-methyl CAS# 63148-62-9, BENZYL ALCOHOL CAS# 100-51-6, Alky Quaternary Ammonium Bentonite CAS# 68953-58-2, HYDROCARBON RESIN-NON-HAZARDOUS, Naphthalene CAS# 91-20-3, HYDROXY MODIFIED RESIN-NON-HAZARDOUS, COLORS MAY CONTAIN: Titanium Dioxide CAS# 13463-67-7, CARBON CAS# 1333-86-4, Silicon Dioxide CAS# 7631-86-9, Ferric Oxide CAS# 1309-37-1, Iron III hydroxide CAS# 20344-49-4, Yellow Pigment CAS# not available, Zinc Sulfide (component of yellow pigment) CAS# 1314-98-3, Barium Sulfate (component of yellow pigment) CAS# 7727-43-7, Pigment yellow 65 (component of yellow pigment) CAS# 6528-34-3, C.I. Pigment Blue CAS# 147-14-8, Aluminum Oxide CAS# 1344-28-1, Iron Oxide Yellow CAS# 51274-00-1.

**APPLICATION PROCEDURES:**

Request and read the technical data sheet before use. Properly prepare the surface to be coated. Make sure the product is applied with temperatures between 50-80 degrees F with relative humidity below 90%. Store material at room temperature before using. Apply a suitable primer when needed. Lower temperatures will require more time for material to cure. Check preceding coats and subsequent coats for blushes. Mix the part A and part B together thoroughly (make sure the mix ratio is correct). Apply the material by brush or roller. Apply the material at the recommended thickness to prevent runs and sags.

**DOT:** Part A: Not Regulated. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, AMINO TERMINATER POLYETHER), 8, PG III.

**IMO/IMDG:** Part A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PG III, MARINE POLLUTANT. Part B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, AMINO TERMINATED POLYETHER, NONYL PHENOL), 8, PG III, MARINE POLLUTANT.

**NOTICE TO BUYER:**

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at [www.garonproducts.com](http://www.garonproducts.com)

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. This material has a maximum VOC of 7 grams per liter.