

DANGER!

Harmful if swallowed. Harmful in contact with skin. Causes serious eye damage. May cause an allergic skin reaction. Causes severe skin burns and eye damage. Suspected of damaging fertility of the unborn child.

Toxic to aquatic life.

PRECAUTIONARY STATEMENTS:

Keep out of reach of children. Read label before use. IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell. Rinse mouth. IF ON SKIN: wash with plenty of soap and water. Call a POISON CENTER or doctor/physician if you feel unwell. Take off immediately all contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If in eyes, immediately call a POISON CENTER or doctor/physician. IF SKIN irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

Store locked up. Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

TO FIGHT FIRE:

Fight fire with CO2, foam, dry chemical or water fog. Hazardous decomposition products may be CO2, CO, acids, aldehydes, and NOX compounds or by-products. Fire fighters should wear a self-contained breathing apparatus.



GARON

GARON PRODUCTS, INC
PO BOX 1924, WALL NJ 07719
1-800-631-5380 - www.garonproducts.com

GARON

VERTAPOXY™

For Industrial Use Only

**MIXING: 11.1# PART A TO 3.9# PART B (BY WEIGHT) TWO PARTS
A TO ONE PART B (BY VOLUME) (VOLUMES APPROXIMATE)**

POT LIFE: 150 g mass = 30 to 40 minutes @ 70°F.

HIGHER TEMPERATURES & LARGER VOLUMES DECREASE POT LIFE

Lot Number:

Read carefully other cautions on side panel.
KEEP OUT OF THE REACH OF CHILDREN

HEALTH: 2 **FLAMMABILITY: 1**
REACTIVITY: 0 **PERSONAL PROTECTION: G**

CHEMICAL CONTENT:

TETRAETHYLENE PENTAMINE CAS# 112-57-2, TOFA, REACTION PRODUCTS WITH TEPA CAS# 68953-36-6, DIETHYLENETRIAMINE CAS# 111-40-0, *BISPHENOL A CAS# 80-05-7, HYDROCARBON RESIN NON-HAZARDOUS, Naphthalene CAS# 91-20-3, HYDROXY MODIFIED RESIN NON-HAZARDOUS, Precipitated Silica CAS# 112926-00-8, CARBON CAS# 1333-86-4, Attapulgit clay CAS# 12174-11-7, crystalline silica CAS# 14808-60-7, MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A CAS# 25068-38-6, LIMESTONE CAS# 1317-65-3, Cellulose CAS# 9004-34-6, Kaolin CAS# 1332-58-7, NONYL PHENOL CAS# 25154-52-3, Titanium Dioxide CAS# 13463-67-7, Precipitated Silica CAS# 112926-00-8

APPLICATION PROCEDURES:

Request and read the technical data sheet before use. Properly prepare the substrate. Remove all contaminants including curing compounds. Make sure the surface is dry. Store at room temperature before using. Apply material with temperatures above 60 degrees F. Mix part A and part B together thoroughly using slow speed mixing equipment, jiffy mixer or drill. Product can be used as a bonding agent, or for vertical, horizontal and overhead repairs of cracks and shallow voids. Follow the manufacturers recommendations for proper procedures of each specific application. Product is not UV color stable. Depending on the depth of repair, vertical and overhead repairs can be accomplished easier by adding a clay type product to prevent sags

DOT: PART A: Not Regulated PART B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS TETRAETHYLENE PENTAMINE, DIETHYLENETRIAMINE), 8, PG III

IMO/IMDG: PART A: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PGIII, MARINE POLLUTANT PART B: UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS TETRAETHYLENE PENTAMINE, DIETHYLENETRIAMINE, BISHENOL A), 8, PG III, MARINE POLLUTANT

NOTICE TO BUYER:

Before using this product, request and read all precautions on the MSDS. Before applying this product, read all application and floor preparation instructions on the Product Data Sheet, as it contains our warranty and limits of liability. Product Data Sheets and MSDS are available at www.garonproducts.com

Garon products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended use. However, since such use is beyond our control, we do not guarantee the results to be obtained in the customer's processes. The information contained in this brief is advisory only, and the use of the materials and methods is solely at the risk of the user. These recommendations and suggestions for the use of our materials are in accordance with Garon standards. There are no other warranties by Garon of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product, and under no circumstances, either expressed or implied, will GARON PRODUCTS, INC. be liable for damages in excess of the purchase price of this product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by the officers of manufacturer and direct purchaser or Garon distributor of manufacturer's material. This material has a maximum VOC of zero grams per liter.